www.ntnsnr.ru snr-mail@ya.ru Тел.: (499) 703-40-50

NTN-SNR LINEAR MOTION:
BALL BUSHINGS

NTN SNR

www.ntn-snr.com

With You

As one of the leading manufacturers of rolling bearings in Europe, NTN-SNR has been, for many years, among the most innovative companies within its sector of industry. Since April of 2008, SNR has been a part of a corporate group together with the Japanese company NTN, making it the third largest manufacturer of rolling bearings in the world. Hence, we are able to offer “added value” to our customers with reference to product variety, quality and service. Our company is clearly identified through a world-wide presence and through its continous quality system. Since 1985, we are also active in the market of linear technics. Our extensive line of products within linear technics, our know-how and our made-to-measure services have made us renowned with our customers as a highly efficient partner. It does not matter if for instance it concerns machine components such as ball screws, the attached fixed – and floating bearing units, ball bushings and shafts, or whether you require a linear module as a single-axis or a multi-axes system. NTN-SNR offers you specific and individual customer solution concepts. The NTN-SNR delivery program for ball bushings, shafts and shaft supports offers an extensive variety of DIN ball bearings, as well as models that are completely different. The program is completed by full bearing units including the casing or shaft toolings according to individual customer orders. By way of our wide product program, you will surely be able to find a suitable solution for your application(s). We also provide support with reference to the development of system solutions. Our extensive network of sales and technical engineers will offer you individual advice on-site and they will provide you with specific solutions for your individual application(s).

This technical catalog is the foundation for a meaningful dialogue with you.

We look forward to receiving your order –
We are most happy to welcome you as our customer!

Contents

Ball bushings 4
- ISO dimensions, standard ball bushings, closed 4
- Standard ball bushings, open 6
- Standard ball bushings, adjustable 8
- Standard flanged ball bushings (round) 10
- Tandem standard ball bushings 12
- Tandem flanged standard ball bushings (round) 14
- Middle flanged standard ball bushings (round) 16
- JIS dimensions 18
- Ball bushings, closed 18

Super ball bushings (closed, open) 20

Ball sleeves 22

Linear units with standard ball bushings, relubrication 24
- Linear units with standard ball bushings, closed casing 24
- Linear units with standard ball bushings, closed casing and adjustable clearance 26
- Linear units with standard ball bushings, open casing 28
- Linear units with standard ball bushings, open casing and adjustable clearance 30
- Linear units with standard ball bushings, casing at one side 32
- Linear units with standard ball bushings, casing open on one side and adjustable clearance 34
- Tandem linear units with standard ball bushings, closed casing 36
- Tandem linear units with standard ball bushings, closed casing and adjustable clearance 38
- Tandem linear units with standard ball bushings, open casing 40
- Tandem linear units with standard ball bushings, open casing and adjustable clearance 42
- Quadro linear units with standard ball bushings, closed casing 44
- Quadro linear units with standard ball bushings, open casing 46

Linear units with super ball bushings, relubrication 48
- Linear units with super ball bushings, closed casing 48
- Linear units with super ball bushings, open casing 50
- Linear units with super ball bushings, open casing and adjustable clearance 52
- Tandem linear units with super ball bushings, closed casing 54
- Tandem linear units with super ball bushings, open casing 56
- Tandem linear units with super ball bushings, open casing and adjustable clearance 58

Support rail 60
- Without flange 60
- With flange 61
- For lateral fastening with one row of holes 62
- For lateral fastening with a double row of holes 63

Shaft supports 64

Traverse 65

Shafts 66
- Matrix in function of the pre-selection of solid shafts and hollow shafts 66
- Steel, surface hardness, depth of hardness 66
- Dimension accuracy and tolerance field 66

Solid shafts 67

Hollow shafts 67

Shaft tooling 68
- Examples of tooling 70
- Type designation code 72

General information 74
- Introduction 74
- Load ratings 74
- Relation between the rows of balls and the load rating 75
- Material 76
- Service life 77
- Lubrication and friction 80
- Fittings 82

ISO dimensions

Standard ball bushings, closed

The closed ball bushings of the BBE series according to ISO 10285 are widely utilized in various applications because of their precise cylindrical shape and good operational qualities.

The standard ball bushings can be supplied from stock, with two wiper seals. The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBE12U, BBE12AU
Examples of order reference for a ball bushings with double-sided seal: BBE12UU, BBE12AUU
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBE12UU-RL

Order reference				Dimensions [mm]							
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	B	Tolerance
Plastic cage	Steel cage	Plastic cage	Stainless steel cage								
BBE3	**BBE3A**	**BBES3**	**BBES3A**	3	+0,008 0	7	0 –0,008	10	0 -0,012	–	–
BBE4	**BBE4A**	**BBES4**	**BBES4A**	4		8		12		–	–
BBE5	**BBE5A**	**BBES5**	**BBES5A**	5		12		22	0 -0,2	14,5	0 -0,2
BBE8	**BBE8A**	**BBES8**	**BBES8A**	8		16		25		16,5	
BBE10	**BBE10A**	**BBES10**	**BBES10A**	10		19	0 –0,009	29		22	
BBE12	**BBE12A**	**BBES12**	**BBES12A**	12		22		32		22,9	
BBE16	**BBE16A**	**BBES16**	**BBES16A**	16	+0,009 -0,001	26		36		24,9	
BBE20	**BBE20A**	**BBES20**	**BBES20A**	20		32	0 –0,011	45		31,5	
BBE25	**BBE25A**	**BBES25**	**BBES25A**	25	+0,011 -0,001	40		58	0 -0,3	44,1	0 -0,3
BBE30	**BBE30A**	**BBES30**	**BBES30A**	30		47		68		52,1	
BBE40	**BBE40A**	**BBES40**	**BBES40A**	40	+0,013 -0,002	62	0 –0,013	80		60,6	
BBE50	**BBE50A**	**BBES50**	**BBES50A**	50		75		100		77,6	
BBE60	**BBE60A**	**BBES60**	**BBES60A**	60		90	0 –0,015	125	0 -0,4	101,7	0 -0,4
–	**BBE80A**	–	–	80	+0,016 -0,004	120		165		133,7	



W	Ø D1	Rows of balls	max. eccentri-city, [µm]	max. radial clearance [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
								Standard		Corrosion-resistant	
								Plastic cage	Steel cage	Plastic cage	Stainless steel cage
-	-	4	10	-3	44	105	1,4	**BBE3**	**BBE3-A**	**BBES3**	**BBES3-A**
-	-	4			55	127	2	**BBE4**	**BBE4-A**	**BBES4**	**BBES4-A**
1,1	11,5	4	12		159	265	11	**BBE5**	**BBE5-A**	**BBES5**	**BBES5-A**
1,1	15,2	4			195	402	22	**BBE8**	**BBE8-A**	**BBES8**	**BBES8-A**
1,3	18	4		-4	286	549	36	**BBE10**	**BBE10-A**	**BBES10**	**BBES10-A**
1,3	21	4			419	784	45	**BBE12**	**BBE12-A**	**BBES12**	**BBES12-A**
1,3	24,9	4			432	892	60	**BBE16**	**BBE16-A**	**BBES16**	**BBES16-A**
1,6	30,3	5	15	-6	877	1 370	102	**BBE20**	**BBE20-A**	**BBES20**	**BBES20-A**
1,85	37,5	6			908	1 570	235	**BBE25**	**BBE25-A**	**BBES25**	**BBES25-A**
1,85	44,5	6		-8	1 584	2 740	360	**BBE30**	**BBE30-A**	**BBES30**	**BBES30-A**
2,15	59	6	17		2 357	4 020	770	**BBE40**	**BBE40-A**	**BBES40**	**BBES40-A**
2,65	72	6		-13	4 702	7 940	1 250	**BBE50**	**BBE50-A**	**BBES50**	**BBES50-A**
3,15	86,5	6	20		6 085	9 800	2 220	**BBE60**	**BBE60-A**	**BBES60**	**BBES60-A**
4,15	116	6		-20	9 456	16 000	5 140	**BBE80**	–	–	–

The indicated load ratings are applicable in case the load only applies to one row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased (refer to table on page 75).

Standard ball bushings, open

Where bending (deflection) of the shaft has to be avoided, open standard ball bushings are utilized in combination with shaft supports. This is often the case for applications with extended travel. By way of the combination described above, the stiffness is in fact additionally increased.

The standard ball bushings can be supplied from stock, with two wiper seals. The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBE12U-OP, BBE12AU-OP
Examples of order reference for a ball bushings with double-sided seal: BBE12UU-OP, BBE12AUU-OP
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBE12UU-OP-RL

Order reference				Dimensions [mm]							
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	B	Tolerance
Plastic cage	Steel cage	Plastic cage	Stainless steel cage								
BBE10-OP	**-**	**BBES10-OP**	**-**	10	+0,008 0	19	0 -0,009	29	0 -0,2	22	0 -0,2
BBE12-OP	**BBE12A-OP**	**BBES12-OP**	**BBES12A-OP**	12		22		32		22,9	
BBE16-OP	**BBE16A-OP**	**BBES16-OP**	**BBES16A-OP**	16	+0,009 -0,001	26		36		24,9	
BBE20-OP	**BBE20A-OP**	**BBES20-OP**	**BBES20A-OP**	20		32	0 -0,011	45		31,5	
BBE25-OP	**BBE25A-OP**	**BBES25-OP**	**BBES25A-OP**	25	+0,011 -0,001	40		58	0 -0,3	44,1	0 -0,3
BBE30-OP	**BBE30A-OP**	**BBES30-OP**	**BBES30A-OP**	30		47		68		52,1	
BBE40-OP	**BBE40A-OP**	**BBES40-OP**	**BBES40A-OP**	40	+0,013 -0,002	62	0 -0,013	80		60,6	
BBE50-OP	**BBE50A-OP**	**BBES50-OP**	**BBES50A-OP**	50		75		100		77,6	
BBE60-OP	**BBE60A-OP**	**BBES60-OP**	**BBES60A-OP**	60		90	0 -0,015	125	0 -0,4	101,7	0 -0,4
–	**BBE80A-OP**	–	–	80	+0,016 -0,004	120		165		133,7	



Dimensions [mm]			θ [°]	Rows of balls	max. eccen-tricity [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
									Standard		Corrosion-resistant	
W	ØD1	h							Plastic cage	Steel cage	Plastic cage	Stainless steel cage
1,3	18	6,8	80	3	12	286	549	23	**BBE10-0P**	-	**BBES10-0P**	-
1,3	21	7,5	78	3		416	784	35	**BBE12-0P**	**BBE12A-0P**	**BBES12-0P**	**BBES12A-0P**
1,3	24,9	10	78	3		432	892	48	**BBE16-0P**	**BBE16A-0P**	**BBES16-0P**	**BBES16A-0P**
1,6	30,3	10	60	4	15	877	1 370	84	**BBE20-0P**	**BBE20A-0P**	**BBES20-0P**	**BBES20A-0P**
1,85	37,5	12,5	60	5		908	1 570	195	**BBE25-0P**	**BBE25A-0P**	**BBES25-0P**	**BBES25A-0P**
1,85	44,5	12,5	50	5		1 584	2 740	309	**BBE30-0P**	**BBE30A-0P**	**BBES30-0P**	**BBES30A-0P**
2,15	59	16,8	50	5	17	2 357	4 020	665	**BBE40-0P**	**BBE40A-0P**	**BBES40-0P**	**BBES40A-0P**
2,65	72	21	50	5		4 702	7 940	1 080	**BBE50-0P**	**BBE50A-0P**	**BBES50-0P**	**BBES50A-0P**
3,15	86,5	27,2	54	5	20	6 085	9 800	1 900	**BBE60-0P**	**BBE60A-0P**	**BBES60-0P**	**BBES60A-0P**
4,15	116	36,3	54	5		9 465	16 000	4 380	–	**BBE80A-0P**	–	–

The indicated load ratings for open ball bushings are only applicable where the load is applied from above; if the load is applied from the “open direction“, the load capacity is reduced by the following factor (refer to table on page 75).

Standard ball bushings, adjustable

The slotted standard ball bushings can be built into a casing with an adjustable internal diameter, allowing the clearance between the shaft and the ball bearing to be set.

The standard ball bushings can be supplied from stock, with two wiper seals. The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBE12U-AJ, BBE12AU-AJ
Examples of order reference for a ball bushings with double-sided seal: BBE12UU-AJ, BBE12AUU-AJ
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBE12UU-AJ-RL

Order reference				Dimensions [mm]							
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	B	Tolerance
Plastic cage	Steel cage	Plastic cage	Stainless steel cage								
BBE5-AJ	–	**BBES5-AJ**	–	5	+0,008 0	12	0 -0,008	22	0 -0,2	14,5	0 -0,2
BBE8-AJ	–	**BBES8-AJ**	–	8		16		25		16,5	
BBE10-AJ	–	**BBES10-AJ**	–	10		19	0 -0,009	29		22	
BBE12-AJ	**BBE12A-AJ**	**BBES12-AJ**	**BBES12A-AJ**	12		22		32		22,9	
BBE16-AJ	**BBE16A-AJ**	**BBES16-AJ**	**BBES16A-AJ**	16	+0,009 -0,001	26		36		24,9	
BBE20-AJ	**BBE20A-AJ**	**BBES20-AJ**	**BBES20A-AJ**	20		32	0 -0,011	45		31,5	
BBE25-AJ	**BBE25A-AJ**	**BBES25-AJ**	**BBES25A-AJ**	25	+0,011 -0,001	40		58	0 -0,3	44,1	0 -0,3
BBE30-AJ	**BBE30A-AJ**	**BBES30-AJ**	**BBES30A-AJ**	30		47		68		52,1	
BBE40-AJ	**BBE40A-AJ**	**BBES40-AJ**	**BBES40A-AJ**	40	+0,013 -0,002	62	0 -0,013	80		60,6	
BBE50-AJ	**BBE50A-AJ**	**BBES50-AJ**	**BBES50A-AJ**	50		75		100		77,6	
BBE60-AJ	**BBE60A-AJ**	**BBES60-AJ**	**BBES60A-AJ**	60		90	0 -0,015	125	0 -0,4	101,7	0 -0,4
–	**BBE80A-AJ**	–	–	80	+0,016 -0,004	120		165		133,7	



Dimensions [mm]			Rows of balls	max. eccen-tricity [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
								Standard		Corrosion-resistant	
W	ØD1	h						Plastic cage	Steel cage	Plastic cage	Stainless steel cage
1,1	11,5	1	4	12	159	265	10	**BBE5-AJ**	–	**BBES5-AJ**	–
1,1	15,2	1	4		195	402	19,5	**BBE8-AJ**	–	**BBES8-AJ**	–
1,3	18	1	4		286	549	29	**BBE10-AJ**	–	**BBES10-AJ**	–
1,3	21	1,5	4		416	784	44	**BBE12-AJ**	**BBE12A-AJ**	**BBES12-AJ**	**BBES12A-AJ**
1,3	24,9	1,5	4		432	892	59	**BBE16-AJ**	**BBE16A-AJ**	**BBES16-AJ**	**BBES16A-AJ**
1,6	30,3	2	5	15	877	1 370	100	**BBE20-AJ**	**BBE20A-AJ**	**BBES20-AJ**	**BBES20A-AJ**
1,85	37,5	2	6		908	1 570	230	**BBE25-AJ**	**BBE25A-AJ**	**BBES25-AJ**	**BBES25A-AJ**
1,85	44,5	2	6		1 584	2 740	355	**BBE30-AJ**	**BBE30A-AJ**	**BBES30-AJ**	**BBES30A-AJ**
2,15	59	3	6	17	2 357	4 020	758	**BBE40-AJ**	**BBE40A-AJ**	**BBES40-AJ**	**BBES40A-AJ**
2,65	72	3	6		4 702	7 940	1 230	**BBE50-AJ**	**BBE50A-AJ**	**BBES50-AJ**	**BBES50A-AJ**
3,15	86,5	3	6	20	6 085	9 800	2 170	**BBE60-AJ**	**BBE60A-AJ**	**BBES60-AJ**	**BBES60A-AJ**
4,15	116	3	6		9 465	16 000	5 000	–	**BBE80A-AJ**	–	–

The indicated load ratings are applicable in case the load only applies to one row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

Standard flanged ball bushings (round)

Flanged ball bushings of the BBER series represent a useful addition to the standard ball bushings.

They offer the following advantages:

- The integrated flange design enables a more efficient arrangement of the housing or mounting holes.
- The flanged ball bushings are economical, because fewer components are required and altogether the installation is easier.
- The replacement of the ball bushings is easier.

The standard ball bushings can be supplied from stock, with two wiper seals. The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBER12U, BBER12AU
Examples of order reference for a ball bushings with double-sided seal: BBER12UU, BBER12AUU
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBER12UU-RL

Order reference				Dimensions [mm]								
Standard		Corrosion-resistant		Ød	Tole-rance	ØD	Tole-rance	L	Tole-rance	ØDf	t	ØDp
Plastic cage	Steel cage	Plastic cage	Stainless steel cage									
BBER5	**–**	**BBERS5**	**–**	5	+0,008 0	12	0 -0,013	22	±0,3	28	5	20
BBER8	**BBER8A**	**BBERS8**	**BBERS8A**	8		16		25		32	5	24
BBER12	**BBER12A**	**BBERS12**	**BBERS12A**	12		22	1 -0,016	32		42	6	32
BBER16	**BBER16A**	**BBERS16**	**BBERS16A**	16	+0,009 -0,001	26		36		46	6	36
BBER20	**BBER20A**	**BBERS20**	**BBERS20A**	20		32	0 -0,019	45		54	8	43
BBER25	**BBER25A**	**BBERS25**	**BBERS25A**	25	+0,011 -0,001	40		58		62	8	51
BBER30	**BBER30A**	**BBERS30**	**BBERS30A**	30		47		68		76	10	62
BBER40	**BBER40A**	**BBERS40**	**BBERS40A**	40	+0,013 -0,002	62	0 -0,022	80		98	13	80
BBER50	**BBER50A**	**BBERS50**	**BBERS50A**	50		75		100		112	13	94
BBER60	**BBER60A**	**BBERS60**	**BBERS60A**	60		90	0 -0,025	125		134	18	112
–	**BBER80A**	**–**	**–**	80	+0,016 -0,004	120		165		164	18	142



Dimensions [mm]			Rows of balls	max. eccen-tricity [µm]	Angular deviation [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
									Standard		Corrosion-resistant	
X	Y	Z							Plastic cage	Steel cage	Plastic cage	Stainless steel cage
3,5	6	3,1	4	12	12	159	265	26	**BBER5**	–	**BBERS5**	–
3,5	6	3,1	4			195	402	41	**BBER8**	**BBER8A**	**BBERS8**	**BBERS8A**
4,5	7,5	4,1	4			416	784	80	**BBER12**	**BBER12A**	**BBERS12**	**BBERS12A**
4,5	7,5	4,1	4			432	892	103	**BBER16**	**BBER16A**	**BBERS16**	**BBERS16A**
5,5	9	5,1	5	15	15	877	1 370	182	**BBER20**	**BBER20A**	**BBERS20**	**BBERS20A**
5,5	9	5,1	6			908	1 570	335	**BBER25**	**BBER25A**	**BBERS25**	**BBERS25A**
6,6	11	6,1	6			1 584	2 740	560	**BBER30**	**BBER30A**	**BBERS30**	**BBERS30A**
9	14	8,1	6	17	17	2 357	4 020	1 175	**BBER40**	**BBER40A**	**BBERS40**	**BBERS40A**
9	14	8,1	6			4 702	7 940	1 745	**BBER50**	**BBER50A**	**BBERS50**	**BBERS50A**
11	17	11,1	6	20	20	6 085	9 800	3 220	**BBER60**	**BBER60A**	**BBERS60**	**BBERS60A**
11	17	11,1	6			9 465	16 000	6 420	–	**BBER80A**	–	–

The indicated load ratings are applicable in cases where the load only applies to one row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 73).

Tandem standard ball bushings

The tandem standard ball bushings of the BBE…L series have the same dimensions and tolerances of the ISO standard ball bushings, however they are twice as long and they are applied where high moment load exists.

The big advantage of this type of ball bushings is that two standard ball bushings may be replaced. Since the concentricity is built in, increased accuracy is achieved and manufacturing costs reduced.

The standard ball bushings can be supplied from stock, with two wiper seals. The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBE12LU, BBE12LAU
Examples of order reference for a ball bushings with double-sided seal: BBE12LUU, BBE12LAUU
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBE12LUU-RL

Order reference				Dimensions [mm]							
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	B	Tolerance
Plastic cage	Steel cage	Plastic cage	Stainless steel cage								
BBE8L	**BBE8LA**	**BBES8L**	**BBES8LA**	8	+0,009 0	16	0 -0,009	46	0 -0,3	33	0 -0,3
BBE12L	**BBE12LA**	**BBES12L**	**BBES12LA**	12		22	0 -0,011	61		45,8	
BBE16L	**BBE16LA**	**BBES16L**	**BBES16LA**	16	+0,011 -0,001	26		68		49,8	
BBE20L	**BBE20LA**	**BBES20L**	**BBES20LA**	20		32	0 -0,013	80		61	
BBE25L	**BBE25LA**	**BBES25L**	**BBES25LA**	25	+0,013 -0,002	40		112	0 -0,4	82	0 -0,4
BBE30L	**BBE30LA**	**BBES30L**	**BBES30LA**	30		47		123		104,2	
BBE40L	**BBE40LA**	**BBES40L**	**BBES40LA**	40	+0,016 -0,004	62	0 -0,015	151		121,2	
BBE50L	**BBE50LA**	**BBES50L**	**BBES50LA**	50		75		192		155,2	
BBE60L	**BBE60LA**	**BBES60L**	**BBES60LA**	60		90	0 -0,020	209		170	



Dimensions [mm]		Rows of balls	max. eccen-tri-city [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
							Standard		Corrosion-resistant	
W	ØD1						Plastic cage	Steel cage	Plastic cage	Stainless steel cage
1,1	15,2	4	15	320	804	40	**BBE8L**	**BBE8LA**	**BBES8L**	**BBES8LA**
1,3	21	4		683	1 570	80	**BBE12L**	**BBE12LA**	**BBES12L**	**BBES12LA**
1,3	24,9	4		710	1 780	115	**BBE16L**	**BBE16LA**	**BBES16L**	**BBES16LA**
1,6	30,3	5	17	1 440	2 740	180	**BBE20L**	**BBE20LA**	**BBES20L**	**BBES20LA**
1,85	37,5	6		1 490	3 140	430	**BBE25L**	**BBE25LA**	**BBES25L**	**BBES25LA**
1,85	44,5	6		2 600	5 490	615	**BBE30L**	**BBE30LA**	**BBES30L**	**BBES30LA**
2,15	59	6	20	3 872	8 040	1 400	**BBE40L**	**BBE40LA**	**BBES40L**	**BBES40LA**
2,65	72	6		7 701	15 900	2 320	**BBE50L**	**BBE50LA**	**BBES50L**	**BBES50LA**
3,15	86,5	6	25	9 940	20 000	3 920	**BBE60L**	**BBE60LA**	**BBES60L**	**BBES60LA**

The indicated load ratings are only applicable in cases where the load is being applied to a single row of balls bearing. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

Tandem flanged standard ball bushings (round)

The ball bushings of the BBER…L series combine the advantages of flanged standard ball bushings with those of tandem ball bushings, since they provide a rigid, aligned linear guidance through their length, allowing the application of a second ball bearing.

The standard ball bushings can be supplied from stock, with two wiper seals.
The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BBER12LU, BBER12LAU
Examples of order reference for a ball bushings with double-sided seal: BBER12LUU, BBER12LAUU
Examples of order reference for a ball bushings with double-sided seal, relubricable:BBER12LUU-RL

Order reference				Dimensions [mm]								
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	ØDf	t	ØDp
Plastic cage	Steel cage	Plastic cage	Stainless steel cage									
BBER8L	**BBER8LA**	**BBERS8L**	**BBERS8LA**	8	+0,009 -0,001	16	0 -0,013	46		32	5	24
BBER12L	**BBER12LA**	**BBERS12L**	**BBERS12LA**	12		22	0 -0,016	61		42	6	32
BBER16L	**BBER16LA**	**BBERS16L**	**BBERS16LA**	16	+0,011 -0,001	26		68		46	6	36
BBER20L	**BBER20LA**	**BBERS20L**	**BBERS20LA**	20		32	0 -0,019	80		54	8	43
BBER25L	**BBER25LA**	**BBERS25L**	**BBERS25LA**	25	+0,013 -0,002	40		112	±0,3	62	8	51
BBER30L	**BBER30LA**	**BBERS30L**	**BBERS30LA**	30		47		123		76	10	62
BBER40L	**BBER40LA**	**BBERS40L**	**BBERS40LA**	40	+0,016 -0,004	62	0 -0,022	151		98	13	80
BBER50L	**BBER50LA**	**BBERS50L**	**BBERS50LA**	50		75		192		112	13	94
BBER60L	**BBER60LA**	**BBERS60L**	**BBERS60LA**	60		90	0 -0,025	209		134	18	112



Dimensions [mm]			Rows of balls	max. eccen-tricity [µm]	Angular devi-ation [µm]	dynamic load rating [N]	static load rating [N]	permis-sible statical moment My [Nm]	Weight [g]	Order reference			
										Standard		Corrosion-resistant	
X	Y	Z								Plastic cage	Steel cage	Plastic cage	Stainless steel cage
3,5	6	3,1	4	15	15	320	804	4,3	59	**BBER8L**	**BBER8LA**	**BBERS8L**	**BBERS8LA**
4,5	7,5	4,1	4			683	1 570	12	110	**BBER12L**	**BBER12LA**	**BBERS12L**	**BBERS12LA**
4,5	7,5	4,1	4			710	1 780	14	160	**BBER16L**	**BBER16LA**	**BBERS16L**	**BBERS16LA**
5,5	9	5,1	5	17	17	1 440	2 740	25	260	**BBER20L**	**BBER20LA**	**BBERS20L**	**BBERS20LA**
5,5	9	5,1	6			1 490	3 140	44	540	**BBER25L**	**BBER25LA**	**BBERS25L**	**BBERS25LA**
6,6	11	6,1	6			2 600	5 490	78	815	**BBER30L**	**BBER30LA**	**BBERS30L**	**BBERS30LA**
9	14	8,1	6	20	20	3 872	8 040	147	1 805	**BBER40L**	**BBER40LA**	**BBERS40L**	**BBERS40LA**
9	14	8,1	6			7 701	15 900	396	2 820	**BBER50L**	**BBER50LA**	**BBERS50L**	**BBERS50LA**
11	17	11,1	6	25	25	9 940	20 000	487	4 920	**BBER60L**	**BBER60LA**	**BBERS60L**	**BBERS60LA**

The indicated load ratings are only applicable in cases where the load is being applied to a single row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

Middle flanged standard ball bushings (round)

Tandem ball bushings of the BBERM… series with a middle flange are designed specially for applications in which the shafts are perpendicular to the mounting surface. They remove the need for a housing and simplify the installation.

Optional relubricable

The standard ball bushings can be supplied from stock, with two wiper seals.
The required seals are to be included when ordering.

Examples of order reference for a ball bushings with single-sided seal: BBERM12U, BBERM12AU
Examples of order reference for a ball bushings with double-sided seal: BBERM12UU, BBERM12AUU

Order reference				Dimensions [mm]									
Standard		Corrosion-resistant		Ød	Tolerance	ØD	Tolerance	L	Tolerance	l	ØDf	t	ØDp
Plastic cage	Steel cage	Plastic cage	Stainless steel cage										
BBERM8	**BBERM8A**	**BBERMS8**	**BBERMS8A**	8	+0,009 -0,001	16	0 -0,013	46	±0,3	20,5	32	5	24
BBERM12	**BBERM12A**	**BBERMS12**	**BBERMS12A**	12		22	0 -0,016	61		27,5	42	6	32
BBERM16	**BBERM16A**	**BBERMS16**	**BBERMS16A**	16	+0,011 -0,001	26		68		31	46	6	36
BBERM20	**BBERM20A**	**BBERMS20**	**BBERMS20A**	20		32	0 -0,019	80		36	54	8	43
BBERM25	**BBERM25A**	**BBERMS25**	**BBERMS25A**	25	+0,013 -0,002	40		112		52	62	8	51
BBERM30	**BBERM30A**	**BBERMS30**	**BBERMS30A**	30		47		123		56,5	76	10	62
BBERM40	**BBERM40A**	**BBERMS40**	**BBERMS40A**	40	+0,016 -0,004	62	0 -0,022	151		69	98	13	80
BBERM50	**BBERM50A**	**BBERMS50**	**BBERMS50A**	50		75		192		89,5	112	13	94
BBERM60	**BBERM60A**	**BBERMS60**	**BBERMS60A**	60		90	0 -0,025	209		95,5	134	18	112



Dimensions [mm]			Rows of balls	max. eccen-tricity [µm]	Angular deviation [µm]	dynamic load rating [N]	static load rating [N]	permis-sible statical moment My [Nm]	Weight [g]	Order reference			
										Standard		Corrosion-resistant	
X	Y	Z								Plastic cage	Steel cage	Plastic cage	Stainless steel cage
3,5	6	3,1	4	15	15	320	804	4,3	59	**BBERM8**	**BBERM8A**	**BBERMS8**	**BBERMS8A**
4,5	7,5	4,1	4			683	1 570	11,7	110	**BBERM12**	**BBERM12A**	**BBERMS12**	**BBERMS12A**
4,5	7,5	4,1	4			710	1 780	14,2	160	**BBERM16**	**BBERM16A**	**BBERMS16**	**BBERMS16A**
5,5	9	5,1	5	17	17	1 440	2 740	25	260	**BBERM20**	**BBERM20A**	**BBERMS20**	**BBERMS20A**
5,5	9	5,1	6			1 490	3 140	44	540	**BBERM25**	**BBERM25A**	**BBERMS25**	**BBERMS25A**
6,6	11	6,1	6			2 600	5 490	78,9	815	**BBERM30**	**BBERM30A**	**BBERMS30**	**BBERMS30A**
9	14	8,1	6	20	20	3 872	8 040	147	1 805	**BBERM40**	**BBERM40A**	**BBERMS40**	**BBERMS40A**
9	14	8,1	6			7 701	15 900	396	2 820	**BBERM50**	**BBERM50A**	**BBERMS50**	**BBERMS50A**
11	17	11,1	6	25	25	9 940	20 000	487	4 920	**BBERM60**	**BBERM60A**	**BBERMS60**	**BBERMS60A**

The indicated load ratings are only applicable in cases where the load is being applied to a single row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

JIS dimensions ball bushings, closed

Closed ball bushings of the BB series, according to JIS
(Metric series, Asian dimensions).

The ball bushings with the order reference printed in **bold** are available ex stock.
The required seals are to be included when ordering.

Optional relubricable

Examples of order reference for a ball bushings with single-sided seal: BB12U, BB12AU
Examples of order reference for a ball bushings with double-sided seal: BB12UU, BB12AUU
Examples of order reference for a ball bushings with double-sided seal, relubricable:BB12UU-RL

Order reference				Dimensions [mm]									
Standard		Corrosion-resistant		Ød	Tole-rance	ØD	Tole-rance	L	Tole-rance	B	Tole-rance	W	ØD1
Plastic cage	Steel cage	Plastic cage	Edelsteel cage										
BB3	**BB3A**	**BBS3**	**BBS3A**	3	0 -0,008	7	0 -0,009	10	0 -0,12	-	-	-	-
BB4	**BB4A**	**BBS4**	**BBS4A**	4		8		12		-	-	-	-
BB5	**BB5A**	**BBS5**	**BBS5A**	5		10		15		10,2	0 -0,2	1,1	9,6
BB6	**BB6A**	**BBS6**	**BBS6A**	6	0 -0,009	12	0 -0,011	19	0 -0,2	13,5		1,1	11,5
BB8s	**BB8sA**	**BBS8s**	**BBS8sA**	8		15		17		11,5		1,1	14,3
BB8	**BB8A**	**BBS8**	**BBS8A**	8		15		24		17,5		1,1	14,3
BB10	**BB10A**	**BBS10**	**BBS10A**	10		19	0 -0,013	29		22		1,3	18
BB12	**BB12A**	**BBS12**	**BBS12A**	12		21		30		23		1,3	20
BB13	**BB13A**	**BBS13**	**BBS13A**	13		23		32		23		1,3	22
BB16	**BB16A**	**BBS16**	**BBS16A**	16		28		37		26,5		1,6	27
BB20	**BB20A**	**BBS20**	**BBS20A**	20	0 -0,010	32	0 -0,016	42		30,5		1,6	30,5
BB25	**BB25A**	**BBS25**	**BBS25A**	25		40		59	0 -0,3	41	0 -0,3	1,85	38
BB30	**BB30A**	**BBS30**	**BBS30A**	30		45		64		44,5		1,85	43
BB35	**BB35A**	**BBS35**	**BBS35A**	35	0 -0,012	52	0 -0,019	70		49,5		2,1	49
BB40	**BB40A**	**BBS40**	**BBS40A**	40		60		80		60,5		2,1	57
BB50	**BB50A**	**BBS50**	**BBS50A**	50		80		100		74		2,6	76,5
BB60	**BB60A**	**BBS60**	**BBS60A**	60	0 -0,015	90	0 -0,022	110		85		3,15	86,5
BB80	**BB80A**	**BBS80**	**BBS80A**	80		120		140	0 -0,4	105,5	0 -0,4	4,15	116
–	**BB100A**	–	–	100	0 -0,020	150	0 -0,025	175		125,5		4,15	145
–	**BB120A**	–	–	120		180		200		158,6		4,15	175
––	**BB150A**	–	–	150	0 -0,025	210	0 -0,029	240		170,6		5,15	204



Rows of balls	max. eccentricity [µm]	max. radial clearance [µm]	dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference			
						Standard		Corrosion-resistant	
						Plastic cage	Steel cage	Plastic cage	Stainless steel cage
4	8	-3	44	105	1,4	**BB3**	**BB3A**	**BBS3**	**BBS3A**
4			47	127	2	BB4	BB4A	BBS4	BBS4A
4			82	206	4	BB5	BB5A	BBS5	BBS5A
4	12		131	265	8,5	BB6	BB6A	BBS6	BBS6A
4			153	216	11	BB8s	BB8sA	BBS8s	BBS8sA
4			194	392	17	BB8	BB8A	BBS8	BBS8A
4		-4	286	594	36	BB10	BB10A	BBS10	BBS10A
4			415	784	42	BB12	BB12A	BBS12	BBS12A
4			421	784	49	**BB13**	**BB13A**	**BBS13**	**BBS13A**
4		-6	676	1 180	76	BB16	BB16A	BBS16	BBS16A
5	15		792	1 370	100	BB20	BB20A	BBS20	BBS20A
6			1 073	1 570	240	BB25	BB25A	BBS25	BBS25A
6		-8	1 584	2 740	270	BB30	BB30A	BBS30	BBS30A
6	20		1 875	3 140	425	**BB35**	**BB35A**	**BBS35**	**BBS35A**
6		-10	2 357	4 020	654	BB40	BB40A	BBS40	BBS40A
6		-13	4 702	7 940	1 700	BB50	BB50A	BBS50	BBS50A
6	25		5 606	10 000	2 000	BB60	BB60A	BBS60	BBS60A
6		-20	10 347	16 000	4 520	BB80	BB80A	BBS80	BBS80A
6	30		17 323	34 800	8 600	–	**BB100A**	–	–
8		-25	24 571	40 000	15 000	–	**BB120A**	–	–
8	40		33 701	54 300	20 250	–	**BB150A**	–	–

The indicated load ratings are only applicable in cases where the load is being applied to a single row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

Super ball bushings (closed, open)

The super ball bushings of the BBET series according to ISO 10285 are available as an open and a closed model. The super ball bushings have similar dimensions and tolerances as standard ball bushings.

Super ball bushings have crowned track segments which allow misalignments of up to 0.5° to be accomodated. Hence, overloading because of bending (deflection) of the shaft or skew due to inaccuracies of the tooling hole is avoided.

Through the specific construction, higher capacities, smoother operation, as well as a higher permissible operating speed of up to 3 m/s, are obtained.

Because of the self-adjustment, per shaft, at least two super ball bushings should be utilized to avoid tilting.

The super ball bushings can be supplied from stock, with two wiper seals.
Examples of order reference for a ball bushings with double-sided seal: BBET12UU, BBET12UU-OP

Order reference		Dimensions [mm]									
closed	open	Ødr	Tolerance	ØD	L	Tolerance	L1	Tolerance	L2	ØD1	h
BBET8	**–**	8	+0,008 0	16	25	±0,2	16,5	0 -0,2	1,1	15,2	–
BBET10	**–**	10		19	29		22		1,3	18	–
BBET12	**BBET12-OP**	12		22	32		22,9		1,3	21	6,5
BBET16	**BBET16-OP**	16	+0,009 0,001	26	36		24,9		1,3	24,9	9
BBET20	**BBET20-OP**	20		32	45		31,5		1,6	30,3	9
BBET25	**BBET25-OP**	25	+0,011 0,001	40	58		44,1	0 -0,3	1,85	37,5	11,5
BBET30	**BBET30-OP**	30		47	68		52,1		1,85	44,5	14
BBET40	**BBET40-OP**	40	+0,013 0,002	62	80		60,6		2,15	59	19,5
BBET50	**BBET50-OP**	50		75	100		77,6		2,65	72	22,5



Dimensions [mm]				Rows of balls		dynamic load rating [N]	static load rating [N]	Weight [g]		Order reference	
θ [°]	F H11	G	J	closed	open			closed	open	closed	open
–	–	–	–	4	–	423	534	7,3	–	**BBET8**	
–	–	–	–	5	–	750	935	14	–	**BBET10**	
66	3	–	0,7	5	4	1 020	1 290	21	17	**BBET12**	**BBET12-OP**
68		–	1	5	4	1 250	1 550	43	35	**BBET16**	**BBET16-OP**
55		–	1	6	5	2 090	2 630	58	48	**BBET20**	**BBET20-OP**
57		1,5	1,5	6	5	3 780	4 720	123	103	**BBET25**	**BBET25-OP**
57		2	1,7	6	5	5 470	6 810	216	177	**BBET30**	**BBET30-OP**
56		1,5	2,4	6	5	6 590	8 230	333	275	**BBET40**	**BBET40-OP**
54	5	2,5	2,7	6	5	10 800	13 500	618	520	**BBET50**	**BBET50-OP**

The indicated load ratings are only applicable in cases where the load is being applied to a single row of balls. If, however, the force is shared between two rows of balls, the load capacity is increased by the following factor (refer to table on page 75).

Ball sleeves

The ball sleeves of the KH series are compact linear ball bearings with small dimensions similar to sleeve bearings.

The balls, circulating in the retainer pass via openings in the outer sleeve, allowing relubrication.

The ball sleeves with the order reference printed in **bold** are also available with two wiper seals. The required seals are to be included when ordering.

Example of order reference for a ball bearing with double-sided seal: KH1228LL/3AS



Order reference	Dimensions [mm]			Rows of ball bushings	dynamic load rating [N]	static load rating [N]	Weight [g]
	Ød	ØD	B				
KH1228	12	19	28	5	605	495	18
KH1428	14	21	28	5	600	505	21
KH1630	16	24	30	5	775	600	27
KH2030	20	28	30	6	1 050	880	33
KH2540	25	35	40	6	1 930	1 560	66
KH3050	30	40	50	7	2 700	2 450	95
KH4060	40	52	60	8	4 250	4 000	180
KH5070	50	62	70	9	5 300	5 700	240

Linear units with standard ball bushings, relubrication



Linear units with standard ball bushings, closed casing

Due to their optimised design, the linear units of the LSE series with a relubrication system offer high precision in any type of installation.

A LSE linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE standard ball bushings
- wiper seals made from NBR

The linear units offer substantial cost advantages to the user, because of reduced construction expense.

The unit construction allows easier integration into installations. Reduced unit weight is obtained by using high grade aluminium, allowing for greater accelerations and higher speeds.

Order reference	Dimensions [mm]									
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	G	Y	B	C
LSE12UU	12	22	18	43	39	35	25	10	32	23
LSE16UU	16	26	22	53	43	42	30	12	40	26
LSE20UU	20	32	25	60	54	50	34	13	45	32
LSE25UU	25	40	30	78	67	60	40	15	60	40
LSE30UU	30	47	35	87	79	70	48	16	68	45
LSE40UU	40	62	45	108	91	90	60	20	86	58



Dimensions [mm]				dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	P	K	S				
M5	8	11	4,2	416	784	175	**LSE12UU**
M6	10	13	5,2	432	892	260	**LSE16UU**
M8	11	18	6,8	877	1 370	442	**LSE20UU**
M10	15	22	8,6	908	1 570	885	**LSE25UU**
M10	15	22	8,6	1 584	2 740	1330	**LSE30UU**
M12	18	26	10,3	2 357	4 020	2 570	**LSE40UU**

Linear units with standard ball bushings, closed casing and adjustable clearance



The LSE…-AJ series of linear units are used where guidance with pretension or without play is required. An adjusting screw allows the radial clearance to be set.

A LSE...-AJ linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE...-AJ standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]										
	Ød	ØD H6	H	+0,01 -0,02	W	L	+0,3	F	G	Y	B	C
LSE12UU-AJ	12	22	18		43	39		35	25	10	32	23
LSE16UU-AJ	16	26	22		53	43		42	30	12	40	26
LSE20UU-AJ	20	32	25		60	54		50	34	13	45	32
LSE25UU-AJ	25	40	30		78	67		60	40	15	60	40
LSE30UU-AJ	30	47	35		87	79		70	48	16	68	45
LSE40UU-AJ	40	62	45		108	91		90	60	20	86	58



Dimensions [mm]				dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	P	K	S				
M5	8	11	4,2	416	784	175	**LSE12UU-AJ**
M6	10	13	5,2	432	892	260	**LSE16UU-AJ**
M8	11	18	6,8	877	1 370	442	**LSE20UU-AJ**
M10	15	22	8,6	908	1 570	885	**LSE25UU-AJ**
M10	15	22	8,6	1 584	2 740	1 330	**LSE30UU-AJ**
M12	18	26	10,3	2 357	4 020	2 570	**LSE40UU-AJ**

Linear units with standard ball bushings, open casing

The LSE…-OP series of linear units are used on long shafts which are fully supported. These linear units provide high rigidity and their unit construction allows easier integration into an installation.

A LSE...-OP linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]									
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	G	Y	T	B
LSE12UU-OP	12	22	18	43	39	28	23,5	8	16,65	32
LSE16UU-OP	16	26	22	53	43	35	30	12	22	40
LSE20UU-OP	20	32	25	60	54	42	34	13	25	45
LSE25UU-OP	25	40	30	78	67	51	40	15	31,5	60
LSE30UU-OP	30	47	35	87	79	60	48	16	33	68
LSE40UU-OP	40	62	45	108	91	77	60	20	43,5	86



Dimensions [mm]						dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
C	M	P	K	S	R +0,6				
23	M5	8	11	4,2	7	416	784	145	**LSE12UU-OP**
26	M6	10	13	5,2	9,4	432	892	218	**LSE16UU-OP**
32	M8	11	18	6,8	10,2	877	1 370	384	**LSE20UU-OP**
40	M10	15	22	8,6	12,5	908	1 570	765	**LSE25UU-OP**
45	M10	15	22	8,6	13,9	1 584	2 740	1 170	**LSE30UU-OP**
58	M12	18	26	10,3	18	2 357	4 020	2 265	**LSE40UU-OP**

Linear units with standard ball bushings, open casing and adjustable clearance

The LSE…-AO series of linar units are used where guidance with pre-tension or without play is required.

An adjusting screw allows the radial clearance to be set.

A LSE...-AO linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]									
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	G	Y	T	B
LSE12UU-AO	12	22	18	43	39	28	25	8	16,65	32
LSE16UU-AO	16	26	22	53	43	35	30	12	22	40
LSE20UU-AO	20	32	25	60	54	42	34	13	25	45
LSE25UU-AO	25	40	30	78	67	51	40	15	31,5	60
LSE30UU-AO	30	47	35	87	79	60	48	16	33	68
LSE40UU-AO	40	62	45	108	91	77	60	20	43,5	86



Dimensions [mm]						dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
C	M	P	K	S	R +0,6				
23	M5	8	11	4,2	7	416	784	145	**LSE12UU-AO**
26	M6	10	13	5,2	9,4	432	892	218	**LSE16UU-AO**
32	M8	11	18	6,8	10,2	877	1 370	384	**LSE20UU-AO**
40	M10	15	22	8,6	12,5	908	1 570	765	**LSE25UU-AO**
45	M10	15	22	8,6	13,9	1 584	2 740	1 170	**LSE30UU-AO**
58	M12	18	26	10,3	18	2 357	4 020	2 265	**LSE40UU-AO**

Linear units with standard ball bushings, casing at one side

Normally, with the open ball bushings design, if the load is applied against the 'open direction', substantial reductions in the load capacity occur.

The linear units of the LSE…-SOP series are designed to handle forces in all directions, without a reduction in the load capacity.

A LSE...-SOP linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]									
	Ød	ØD H6	H ±0,015	W	L +0,3	F	G	T +0,02 -0,02	C	
LSE20UU-SOP	20	32	30	60	54	60	42	17	30	
LSE25UU-SOP	25	40	35	75	67	72	50	21	36	
LSE30UU-SOP	30	47	40	86	79	82	55	25	42	
LSE40UU-SOP	40	62	45	110	91	100	67	32	48	



Dimensions [mm]						dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	K	S	R +0,6	X	Y				
M10	22	8,6	10,2	23,5	32	877	1 370	504	**LSE20UU-SOP**
M12	26	10,3	12,5	29	38	908	1 570	995	**LSE25UU-SOP**
M16	34	13,5	13,9	34	44	1 584	2 740	1 510	**LSE30UU-SOP**
M20	43	17,5	18	40	50	2 357	4 020	2 665	**LSE40UU-SOP**

Linear units with standard ball bushings, casing open on one side and adjustable clearance

Normally, with the open ball bushings design, if the load is applied against the 'open direction', substantial reductions in the load capacity occur.

The linear units of the LSE…-SAO series are designed to handle forces in all directions, without a reduction in the load capacity.

Radial clearance can be set by means of an adjusting screw.

A LSE...-SAO linear unit consists of the following:

- casing (AlMgSi0,5)
- BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]									
	Ød	ØD H6	H ±0,015	W	L ±0,3	F	G	T ±0,02	C	
LSE20UU-SAO	20	32	30	60	54	60	42	17	30	
LSE25UU-SAO	25	40	35	75	67	72	50	21	36	
LSE30UU-SAO	30	47	40	86	79	82	55	25	42	
LSE40UU-SAO	40	62	45	110	91	100	67	32	48	



Dimensions [mm]						dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	K	S	R +0,6	X	Y				
M10	22	8,6	10,2	23,5	32	877	1 370	504	**LSE20UU-SA0**
M12	26	10,3	12,5	29	38	908	1 570	995	**LSE25UU-SA0**
M16	34	13,5	13,9	34	44	1 584	2 740	1 510	**LSE30UU-SA0**
M20	43	17,5	18	40	50	2 357	4 020	2 665	**LSE40UU-SA0**

Tandem linear units with standard ball bushings, closed casing

The tandem linear units of the LSE…L series are twice as long as those of the LSE series. They can be utilized in applications where high moment loads exist.

A LSE…L linear unit consists of the following:

- casing (AlMgSi0,5)
- two standard BBE ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]								
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	G	B	C
LSE12LUU	12	22	18	43	76	35	25	32	56
LSE16LUU	16	26	22	53	84	42	30	40	64
LSE20LUU	20	32	25	60	104	50	34	45	76
LSE25LUU	25	40	30	78	130	60	40	60	94
LSE30LUU	30	47	35	87	152	70	48	68	106
LSE40LUU	40	62	45	108	176	90	60	86	124



Dimensions [mm]				dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	P	K	S				
M5	8	11	4,2	683	1 570	360	**LSE12LUU**
M6	10	13	5,2	710	1 780	530	**LSE16LUU**
M8	11	18	6,8	1 440	2 740	920	**LSE20LUU**
M10	15	22	8,6	1 490	3 140	1 820	**LSE25LUU**
M10	15	22	8,6	2 600	5 490	2 730	**LSE30LUU**
M12	18	26	10,3	3 872	8 040	5 210	**LSE40LUU**

Tandem linear units with standard ball bushings, closed casing and adjustable clearance



The linear units of the LSE…L-AJ series are twice as long as those of the LSE…AJ series. They are utilized where guidance with pretension or without play is required.

A LSE...L-AJ linear unit consists of the following:
- casing (AlMgSi0,5)
- two standard BBE...-AJ ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]										
	ød	ØD H6	H +0,01 -0,02	W	L	+0,3	F	G	Y	B	C
LSE12LUU-AJ	12	22	18	43	76		35	25	10	32	56
LSE16LUU-AJ	16	26	22	53	84		42	30	12	40	64
LSE20LUU-AJ	20	32	25	60	104		50	34	13	45	76
LSE25LUU-AJ	25	40	30	78	130		60	40	15	60	94
LSE30LUU-AJ	30	47	35	87	152		70	48	16	68	106
LSE40LUU-AJ	40	62	45	108	176		90	60	20	86	124



Dimensions [mm]				dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
M	P	K	S				
M5	8	11	4,2	683	1 570	360	**LSE12LUU-AJ**
M6	10	13	5,2	710	1 780	530	**LSE16LUU-AJ**
M8	11	18	6,8	1 440	2 740	920	**LSE20LUU-AJ**
M10	15	22	8,6	1 490	3 140	1 820	**LSE25LUU-AJ**
M10	15	22	8,6	2 600	5 490	2 730	**LSE30LUU-AJ**
M12	18	26	10,3	3 872	8 040	5 210	**LSE40LUU-AJ**

Tandem linear units with standard ball bushings, open casing

The tandem linear units of the LSE…L-OP series are twice as long as those of the LSE...-OP series. They can be used where high moment loads exist, on long fully supported shafts.

A LSE…L-OP linear unit consists of the following:
- casing (AlMgSi0,5)
- two BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]										
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3		F	G	Y	X	T
LSE12LUU-OP	12	22	18	43	76		30	25	8	19,5	16,65
LSE16LUU-OP	16	26	22	53	84		35	30	12	21,5	22
LSE20LUU-OP	20	32	25	60	104		42	34	13	27	25
LSE25LUU-OP	25	40	30	78	130		51	40	15	33,5	31,5
LSE30LUU-OP	30	47	35	87	152		60	48	16	39,5	33
LSE40LUU-OP	40	62	45	108	176		77	60	20	45,5	43,5



Dimensions [mm]							dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	P	K	S	R +0,6				
32	56	M5	8	11	4,2	7	683	1 570	290	**LSE12LUU-OP**
40	64	M6	10	13	5,2	9,4	710	1 780	440	**LSE16LUU-OP**
45	76	M8	11	18	6,8	10,2	1 440	2 740	790	**LSE20LUU-OP**
60	94	M10	15	22	8,6	12,9	1 490	3 140	1 560	**LSE25LUU-OP**
68	106	M10	15	22	8,6	14,4	2 600	5 490	2 300	**LSE30LUU-OP**
86	124	M12	18	34	10,3	18,2	3 872	8 040	4 500	**LSE40LUU-OP**

Tandem linear units with standard ball bushings, open casing and adjustable clearance

The linear units of the LSE…L-AO series are twice as long as those of the LSE…AO series.
They are utilized in guidance systems with pre-tension or without play where moment loads exist.

A LSE...L-AO linear unit consists of the following:
- casing (AlMgSi0,5)
- two BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]										
	ød	ØD H6	H +0,01 -0,02	W	L	+0,3	F	G	Y	X	T
LSE12LUU-AO	12	22	18	43	76		30	25	8	19,5	16,65
LSE16LUU-AO	16	26	22	53	84		35	30	12	21,5	22
LSE20LUU-AO	20	32	25	60	104		42	34	13	27	25
LSE25LUU-AO	25	40	30	78	130		51	40	15	33,5	31,5
LSE30LUU-AO	30	47	35	87	152		60	48	16	39,5	33
LSE40LUU-AO	40	62	45	108	176		77	60	20	45,5	43,5



Dimensions [mm]							dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	P	K	S	R +0,6				
32	56	M5	8	11	4,2	7	683	1 570	290	**LSE12LUU-AO**
40	64	M6	10	13	5,2	9,4	710	1 780	440	**LSE16LUU-AO**
45	76	M8	11	18	6,8	10,2	1 440	2 740	790	**LSE20LUU-AO**
60	94	M10	15	22	8,6	12,5	1 490	3 140	1 560	**LSE25LUU-AO**
68	106	M10	15	22	8,6	13,9	2 600	5 490	2 300	**LSE30LUU-AO**
86	124	M12	18	26	10,3	18	3 872	8 040	4 500	**LSE40LUU-AO**

Quadro linear units with standard ball bushings, closed casing

Quadro linear units of the LSE…Q series enable compact and simple table constructions. Details of shaft blocks (slides, supports) can be found on pages 65.

A LSE...Q linear unit consists of the following:

- casing (AlMgSi0,5)
- four BBE standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]							
	ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	Y	A ±0,02
LSE12QUU	12	22	16	85	85	32	13	42
LSE16QUU	16	26	18	100	100	36	15	54
LSE20QUU	20	32	23	130	130	46	19	72
LSE25QUU	25	40	28	160	160	56	24	88
LSE30QUU	30	47	32	180	180	64	27	96
LSE40QUU	40	62	40	230	230	80	35	122



Dimensions [mm]					dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S				
73	73	M6	13	5,3	1 300	2 000	700	**LSE12QUU**
88	88	M6	13	5,3	1 400	2 200	1 020	**LSE16QUU**
115	115	M8	18	6,8	3 200	4 900	2 150	**LSE20QUU**
140	140	M10	22	9	5 500	8 500	4 070	**LSE25QUU**
158	158	M12	26	10,5	6 200	9 500	5 870	**LSE30QUU**
202	202	M16	34	13,5	10 500	14 000	11 780	**LSE40QUU**

Quadro linear units with standard ball bushings, open casing

Quadro linear units of the LSE…Q-OP series enable compact and simple linear conveying or table constructions.

A LSE...Q-OP linear unit consists of the following:
- casing (AlMgSi0,5)
- four BBE…-OP standard ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]							
	Ød	ØD H6	H +0,01 -0,02	W	L +0,3	F	Y	A ±0,02
LSE12QUU-OP	12	22	18	85	85	30	13	42
LSE16QUU-OP	16	26	22	100	100	35	15	54
LSE20QUU-OP	20	32	25	130	130	42	19	72
LSE25QUU-OP	25	40	30	160	160	51	24	88
LSE30QUU-OP	30	47	35	180	180	60	27	96
LSE40QUU-OP	40	62	45	230	230	77	35	122



Dimensions [mm]						dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S	R				
73	73	M6	13	5,3	7	1 300	2 000	590	**LSE12QUU-OP**
88	88	M6	13	5,3	9,4	1 400	2 200	920	**LSE16QUU-OP**
115	115	M8	18	6,8	10,2	3 200	4 900	1 820	**LSE20QUU-OP**
140	140	M10	22	9	12,9	5 500	8 500	3 460	**LSE25QUU-OP**
158	158	M12	26	10,5	13,9	6 200	9 500	5 190	**LSE30QUU-OP**
202	202	M16	34	13,5	18,2	10 500	14 000	10 780	**LSE40QUU-OP**

Linear units with super ball bushings, relubrication

Linear units with super ball bushings, closed casing

Due to their design, the linear units of the LSET series with a relubrication system offer high precision in any type of installation.

A LSET linear unit consists of the following:
- casing (AlMgSi0,5)
- BBET super ball bushings
- wiper seals made from NBR

The linear units offer substantial cost advantages to the user, because of reduced construction expenses.

The unit construction allows easier integration into installations. Reduced unit weight is obtained by using high grade aluminium, allowing for greater acceleration and higher speeds.

Order reference	Dimensions [mm]									
	Ød	H ±0,015	E ±0,015	W	L	F	G	T	X	Y
LSET8UU	8	15	17,5	35	32	28	22	5	-	-
LSET10UU	10	16	20	40	36	31,5	25	5	-	-
LSET12UU	12	18	21,5	43	39	35	28	5	-	-
LSET16UU	16	22	26,5	53	43	42	35	5	-	-
LSET20UU	20	25	30	60	54	50	42	5	19	9
LSET25UU	25	30	39	78	67	60	48	7	22,5	10
LSET30UU	30	35	43,5	87	79	70	58	8	26	11,5
LSET40UU	40	45	54	108	91	90	72	10	26,5	14



Dimensions [mm]					dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S				
25	20	M4	9	3,3	423	534	59	**LSET8UU**
29	20	M5	11	4,3	750	935	90	**LSET10UU**
32	23	M5	11	4,3	1 020	1 290	116	**LSET12UU**
40	26	M6	13	5,3	1 250	1 550	205	**LSET16UU**
45	32	M8	18	6,6	2 090	2 630	326	**LSET20UU**
60	40	M10	22	8,4	3 780	4 720	624	**LSET25UU**
68	45	M10	22	8,4	5 470	6 810	980	**LSET30UU**
86	58	M12	26	10,5	6 590	8 230	1670	**LSET40UU**

Linear units with super ball bushings, open casing

The linear units of the LSET…-OP series with the re-lubricating option are used on long shafts which are fully supported. They offer a high level of rigidity and handle loads in all directions. The unit design allows for simpler integration into the installations.

A LSET…-OP linear unit consists of the following:

- casing (AlMgSi0,5)
- a BBET…-OP super ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]										
	Ød	H ±0,015	E ±0,015	W	L	G	T	R	θ°	X	Y
LSET12UU-OP	12	18	21,5	43	39	28	5	6,5	66	14,5	7,5
LSET16UU-OP	16	22	26,5	53	43	35	5	9	68	15,5	9,5
LSET20UU-OP	20	25	30	60	54	42	5	9	55	19	9
LSET25UU-OP	25	30	39	78	67	51	7	11,5	57	22,5	10
LSET30UU-OP	30	35	43,5	87	79	60	8	14	57	26	11,5
LSET40UU-OP	40	45	54	108	91	77	10	19,5	56	26,5	14



Dimensions [mm]							dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S	P	J				
32	23	M5	11	4,3	8	4,5	1 020	1 290	99	**LSET12UU-OP**
40	26	M6	13	5,3	9,5	5,5	1 250	1 550	175	**LSET16UU-OP**
45	32	M8	18	6,6	11	6,5	2 090	2 630	275	**LSET20UU-OP**
60	40	M10	22	8,4	14	8,6	3 780	4 720	558	**LSET25UU-OP**
68	45	M10	22	8,4	14	8,6	5 470	6 810	860	**LSET30UU-OP**
86	58	M12	26	10,5	17,5	10,8	6 590	8 230	1 490	**LSET40UU-OP**

Linear units with super ball bushings, open casing and adjustable clearance

The linear units of the LSET…-AO series are used where guidance with pretension or with play is required, Radial clearance can be set by means of an adjusting screw,

A LSET...-AO linear unit consists of the following:
- casing (AlMgSi0,5)
- a BBET…-OP super ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]												
	Ød	H ±0,015	E ±0,015	W	L	F	G	Z	T	R	θ°	X	Y
LSET12UU-AO	12	18	21,5	43	39	28	3,2	5	5	6,5	66	14,5	7,5
LSET16UU-AO	16	22	26,5	53	43	35	3,2	6	5	9	68	15,5	9,5
LSET20UU-AO	20	25	30	60	54	42	4,5	8	5	9	55	19	9
LSET25UU-AO	25	30	39	78	67	51	5,5	10	7	11,5	57	22,5	10
LSET30UU-AO	30	35	43,5	87	79	60	5,5	12	8	14	57	26	11,5
LSET40UU-AO	40	45	54	108	91	77	5	15	10	19,5	56	26,5	14



Dimensions [mm]							dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S	P	J				
32	23	M5	11	4,3	8	11,5	1 020	1 290	99	**LSET12UU-AO**
40	26	M6	13	5,3	9,5	14	1 250	1 550	175	**LSET16UU-AO**
45	32	M8	18	6,6	11	18	2 090	2 630	275	**LSET20UU-AO**
60	40	M10	22	8,4	14	22	3 780	4 720	558	**LSET25UU-AO**
68	45	M10	22	8,4	14	26	5 470	6 810	860	**LSET30UU-AO**
86	58	M12	26	10,5	17,5	33	6 590	8 230	1 490	**LSET40UU-AO**

Tandem linear units with super ball bushings, closed casing



The tandem linear units of the LSET…L series are twice as long as those of the LSET series. They can be used where high moment loads exist.

A LSET…L linear unit consists of the following:

- casing (AlMgSi0,5)
- two BBET super ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]								
	Ød	H ±0,015	E ±0,015	W	L	F	G	T	Y
LSET8LUU	8	15	17,5	35	62	28	22	5	6,5
LSET10LUU	10	16	20	40	70	31,5	25	5	7
LSET12LUU	12	18	21,5	43	76	35	28	5	7,5
LSET16LUU	16	22	26,5	53	84	42	35	5	9,5
LSET20LUU	20	25	30	60	104	50	42	5	9
LSET25LUU	25	30	39	78	130	60	48	7	10
LSET30LUU	30	35	43,5	87	152	70	58	8	11,5
LSET40LUU	40	45	54	108	176	90	72	10	14



Dimensions [mm]					dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S				
25	50	M4	9	3,3	685	1 068	119	**LSET8LUU**
29	52	M5	11	4,3	1 215	1 870	175	**LSET10LUU**
32	56	M5	11	4,3	1 652	2 580	227	**LSET12LUU**
40	64	M6	13	5,3	2 025	3 100	390	**LSET16LUU**
45	76	M8	18	6,6	3 390	5 260	630	**LSET20LUU**
60	94	M10	22	8,4	6 120	9 440	1 210	**LSET25LUU**
68	106	M10	22	8,4	8 860	13 620	1 880	**LSET30LUU**
86	124	M12	26	10,5	10 680	16 460	3 280	**LSET40LUU**

Tandem linear units with super ball bushings, open casing

The tandem linear units of the LSET…L-OP series are twice as long as those of the LSET…-OP series. They can be used where high moment loads exist on long shaft which are fully supported.

A LSET…L-OP linear unit consists of the following:

- casing (AlMgSi0,5)
- two BBET…-OP super ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]									
	Ød	H ±0,015	E ±0,015	W	L	G	T	R	θ°	Y
LSET12LUU-OP	12	18	21,5	43	76	28	5	6,5	66	7,5
LSET16LUU-OP	16	22	26,5	53	84	35	5	9	68	9,5
LSET20LUU-OP	20	25	30	60	104	42	5	9	55	9
LSET25LUU-OP	25	30	39	78	130	51	7	11,5	57	10
LSET30LUU-OP	30	35	43,5	87	152	60	8	14	57	11,5
LSET40LUU-OP	40	45	54	108	176	77	10	19,5	56	14



Dimensions [mm]							dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
B	C	M	K	S	P	J				
32	56	M5	11	4,3	8	4,5	1 652	2 580	190	**LSET12LUU-OP**
40	64	M6	13	5,3	9,5	5,5	2 025	3 100	312	**LSET16LUU-OP**
45	76	M8	18	6,6	11	6,5	3 390	5 260	505	**LSET20LUU-OP**
60	94	M10	22	8,4	14	8,6	6 120	9 440	1 050	**LSET25LUU-OP**
68	106	M10	22	8,4	14	8,6	8 860	13 620	1 630	**LSET30LUU-OP**
86	124	M12	26	10,5	17,5	10,8	10 680	16 460	2 880	**LSET40LUU-OP**

Tandem linear units with super ball bushings, open casing and adjustable clearance



The linear units of the LSET…L-AO series are twice as long as those of the LSET…AO series.
They are utilized in guidance systems with pretension or without play where moment loads exist.

A LSET...L-AO linear unit consists of the following:
- casing (AlMgSi0,5)
- two BBET…-OP super ball bushings
- wiper seals made from NBR

Order reference	Dimensions [mm]												
	ød	H ±0,015	E ±0,015	W	L	F	G	Z	A	N	T	R	θ°
LSET12LUU-AO	12	18	21,5	43	76	28	3,2	5	19,5	37	5	6,5	66
LSET16LUU-AO	16	22	26,5	53	84	35	3,2	6	21,5	41	5	9	68
LSET20LUU-AO	20	25	30	60	104	42	4,5	8	27	50	5	9	55
LSET25LUU-AO	25	30	39	78	130	51	5,5	10	33,5	63	7	11,5	57
LSET30LUU-AO	30	35	43,5	87	152	60	5,5	12	39,5	73	8	14	57
LSET40LUU-AO	40	45	54	108	176	77	5	15	45,5	85	10	19,5	56



Dimensions [mm]								dynamic load rating [N]	static load rating [N]	Weight [g]	Order reference
Y	B	C	M	K	S	P	J				
7,5	32	56	M5	11	4,3	8	11,5	1 652	2 580	190	**LSET12LUU-A0**
9,5	40	64	M6	13	5,3	9,5	14	2 025	3 100	312	**LSET16LUU-A0**
9	45	76	M8	18	6,6	11	18	3 390	5 260	505	**LSET20LUU-A0**
10	60	94	M10	22	8,4	14	22	6 120	9 440	1 050	**LSET25LUU-A0**
11,5	68	106	M10	22	8,4	14	26	8 860	13 620	1 630	**LSET30LUU-A0**
14	86	124	M12	26	10,5	17,5	33	10 680	16 460	2 880	**LSET40LUU-A0**

Support rail

Without flange

For supporting shafts in applications utilizing open ball bushings, shaft supports made of an aluminium alloy are available.

The shaft supports without 'SR' flange are suitable for constructions in which the shaft can be mounted from below.

For continuous support, the shaft supports can be installed one behind the other. It is possible to shorten them to the required length, if only partial support is required.



Order reference	Dimensions [mm]												
	Ød	H ±0,02	h	B ±0,02	B1 ±0,02	T	R	M	a	P	N	L max	Weight in case of max. length [g]
SR10-12	12	14,5	15,5	11	5,5	3	5,4	M4	4,5	75	37,5	2 400	440
SR10-16	16	18	16	14	7	3	7	M5	5,5	75	37,5	2 400	540
SR10-20	20	22	20	17	8,5	3	8,1	M6	6,6	75	37,5	2 400	810
SR10-25	25	26	25	21	10,5	3	10,3	M8	9	75	37,5	2 400	1 060
SR10-30	30	30	30	23	11,5	3	11	M10	11	100	50	2 400	1 250
SR10-40	40	39	38	30	15	4	15	M12	13,5	100	50	2 400	2 160
SR10-50	50	46	45	35	17,5	5	19	M14	15,5	100	50	2 400	2 941

Shafts must be ordered separately.

Order designation for support rail with mounted shaft, s. page 73.

With flange

For supported shaft applications involving open ball bushings, shaft supports made of an aluminium alloy are available.

For continuous support, the shaft supports can be installed one behind the other.
It is possible to shorten them to the required length, if only partial support is required.



Order reference	Dimensions [mm]																
	ød	H ±0,02	B	C ±0,15	T	R -0,3	a	b	M	S	(°)	P1	P2	N1	N2	L max	Weight in case of max. length [g]
SR20-12	12	22	40	29	5	5,8	8	5	4,5	4,5	50	75	120	37,5	60	599,5	520
SR20-16	16	26	45	33	5	7	9.5	6	5,5	5,5	50	100	150	50	75	599,5	640
SR20-20	20	32	52	37	6	8,3	11	6,5	6,6	6,6	50	100	150	50	75	599,5	900
SR20-25	25	36	57	42	6	10,8	14	8,5	6,6	9	50	120	200	60	100	599,5	1 080
SR20-30	30	42	69	51	7	11	17	10,5	9	11	50	150	200	75	100	599,5	1 430
SR20-40	40	50	73	55	8	15	17	10,5	9	11	50	200	300	100	150	599,5	1 810
SR20-50	50	60	84	63	9	19	19	12,5	11	13	40	200	300	100	150	599,5	2 450

P1/N1 for applications where the load acts transverse to the ball bushings opening and loading is near the load capacity limit.
P2/N2 for general requirements.

Shafts must be ordered separately.
Order designation for support rail with mounted shaft, s. page 73.

For lateral fastening with one row of holes

Shaft support SR30 is suitable in constructions which utilize linear units with casings open to one side (LSE…-SOP and LSE…-SAO) or open ball bushings.

For continuous support, the shaft supports can be installed one behind the other. It is possible to shorten them to the required length, if only partial support is required.



Order reference	Dimensions [mm]															
	Ød	H	W	T	C	R	ØS	ØM	b	a	P	N	Q	V	L max	Weight in case of max. length [g]
SR30-20	20	52	15	15	7,5	8,3	6,6	11	8,5	8,5	50	25	50	100	599,5	1 100
SR30-25	25	62	20	18	10	10,8	9	15	15	11	60	30	60	120	599,5	1 500
SR30-30	30	72	25	21	12,5	11	11	18	15,3	13,5	75	37,5	75	150	599,5	2 100
SR30-40	40	88	30	25	15	15	14	20	19	16	100	50	100	200	599,5	3 000
SR30-50	50	105	35	30	17,5	19	16	24	21,5	18,5	100	50	100	200	599,5	4 200

Shafts must be ordered separately.

Order designation for support rail with mounted shaft, s. page 73.

For lateral fastening with a double row of holes



Shaft support SR40 is suitable in constructions which utilize linear units with casings open to one side (LSE…-SOP and LSE…-SAO) or open ball bushings.

For continuous support, the shaft supports can be installed one behind the other. It is possible to shorten them to the required length, if only partial support is required.



Order reference	Dimensions [mm]																
	Ød	H	W	T	C	Y	R	ØS	ØM	b	a	P	N	Q	V	L max	Weight in case of max. length [g]
SR40-20	20	52	15	8	7,5	22	8,3	6,6	11	8,5	8,5	37,5	18,75	37,5	75	599,5	1 000
SR40-25	25	62	20	10	10	26	10,8	9	15	15	11	37,5	18,75	37,5	75	599,5	1 300
SR40-30	30	72	25	12	12,5	30	11	11	18	15,3	13,5	50	25	50	100	599,5	1 900
SR40-40	40	88	30	12	15	38	15	14	20	19	16	50	25	50	100	599,5	2 700
SR40-50	50	105	35	15	17,5	45	19	16	24	21,5	18,5	50	25	50	100	599,5	3 700

Shafts must be ordered separately.

Order designation for support rail with mounted shaft, s. page 73.

NTN SNR With You

Shaft supports

Our 'SK' shaft blocks offer a cost-effective solution for clamping shafts.
The shaft blocks are made from aluminium and are characterized by their high rigidity and precision.



Order reference	Dimensions [mm]										Weight [g]
	Ød H8	H	h ±0,02	W	A	B	C±0,15	T	S	J	
SK8	8	27	15	32	16	10	25	5	4,5	3	10
SK12	12	35	20	42	20	12	32	5,5	5,5	3	20
SK16	16	42	25	50	26	16	40	6,5	5,5	3	30
SK20	20	50	30	60	32	20	45	8	5,5	4	70
SK25	25	58	35	74	38	25	60	9	6,6	5	140
SK30	30	68	40	84	45	28	68	10	9	6	200
SK40	40	86	50	108	56	32	86	12	11	8	480
SK50	50	100	60	130	80	40	108	14	11	8	1 900
SK60	60	124	75	160	100	48	132	15	13,5	8	3 600

Traverse

For the quadro-linear units of the LSEQ and LSEQ…-OP series, tandem-shaft blocks are available in two models.

Model A is utilized where the shaft blocks are fixed and the linear blocks moving.

Model B enables moving of the shaft, with the linear unit fixed.



Order reference		Dimensions [mm]											Weight [g]
					H		h ±0,015						
Version A	Version B	Ød	W	B	Version A	Version B	Version A	Version B	C	ØS	M	E	
SH8A	**SH8B**	8	65	12	23	22	12,5	11	52	5,5	M5	32	40
SH12A	**SH12B**	12	85	14	32	28	18	14	70	6,6	M6	42	70
SH16A	**SH16B**	16	100	18	36	32	20	16	82	9	M8	54	130
SH20A	**SH20B**	20	130	20	46	42	25	21	108	11	M10	72	220
SH25A	**SH25B**	25	160	25	56	52	30	26	132	13,5	M12	88	440
SH30A	**SH30B**	30	180	25	64	58	35	29	150	13,5	M12	96	560
SH40A	**SH40B**	40	230	30	80	72	44	36	190	17,5	M16	122	1 000

Shafts

Matrix in function of the pre-selection of solid shafts and hollow shafts

Model	Material	Available shaft diameter [mm]	Standard tolerance of shaft
Solid shaft	Cf53 (1.1213)	4, 5, 6, 8, 10, 12, 16, 20, 25, 30, 35, 40, 50, 60	h6
	X90CrMoV18 (1.4112)	12, 16, 20, 25, 30, 35, 40	h6
	Cf53 (1.1213) hard-chrome plated	12, 16, 20, 25, 30, 35, 40	h7
	X46Cr13 (1.4034)*	12, 16, 20, 25, 30, 35, 40	h6
Hollow shaft	C60 (1.1221)	12, 16, 20, 25, 30, 40, 50, 60	h6

Supply of standard products from stock.

* Please note the limited life duration (s. page 78).

The other models are available upon request.

Steel, surface hardness, depth of hardness

The surfaces of the shafts are induction hardened. The even hardness penetration depth ensures the constant transition of the hardened outer zone from out of the tough, normalized core, capable of coping with bending stress (loads).

Shaft diameter [mm]	from	4	10	18	30	50
	up to	10	18	30	50	80
Min. hardness penetration depth [mm]		0,4	0,6	0,9	1,5	2,2

- heat-treated steel Cf53 (1.1213) with surface hardness HRC 62±2
- stainless and acid-resistant steel X90CrMoV18 (1.4112) with surface hardness HRC 57±2
- hard-chrome plated heat-treated steel Cf53Cr (1.1213) with surface hardness 900-1100HV
- stainless steel X46Cr13 (1.4034) with surface hardness HRC 55±2
- hard-chrome plated heat-treated steel Ck60 (1.1221) with surface hardness HRC 60, thickness of chromium layer apx. 10µm, apx. 1000HV

Dimension accuracy and tolerance field



Nominal diameter [mm]	from	4	6	10	18	30	50
	up to	6	10	18	30	50	80
Roundness tolerance t1 [µm]		4	4	5	6	7	8
Concentricity tolerance t2 [µm]		5	6	8	9	11	13
Straightness-tolerance t3 [µm/m]		150	120	100	100	100	100
Mean deviation [µm]		0,32	0,32	0,32	0,32	0,32	0,32

Details for standard product Cf53 (1.1213)

Solid shafts



Order reference	W04	W05	W06	W08	W10	W12	W16	W20	W25	W30	W35	W40	W50	W60
Diameter d [mm]	4	5	6	8	10	12	16	20	25	30	35	40	50	60
Max. length L [mm]	3600	4000	4000	4000	4000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Mass [kg/m]	0,099	0,154	0,222	0,395	0,617	0,888	1,578	2,466	3,853	5,549	7,552	9,864	15,413	22,195

Details for standard product Cf53 (1.1213)

Hollow shafts



Order reference	HW12	HW16	HW20	HW25	HW30	HW40	HW50	HW60
Diameter d [mm]	12	16	20	25	30	40	50	60
Internal diameter di [mm]	3,4	8	14	14	19	26,5	29,6	36,5
Max. length L [mm]	6000	6000	6000	6000	6000	6000	6000	6000
Mass [kg/m]	0,817	1,184	1,258	2,645	3,323	5,535	10,011	13,981

Details for standard product Ck60 (1.1221)

Shaft tooling

Addition tooling (eg. taps, internal and external threads, countersinks) which require annealing may display minor dimensional changes.

Length tolerance for shortened shafts

Shaft length L [mm]		Max. tolerance [mm]
from	to	
-	400	±0,5
400	1000	±0,8
1000	2000	±1,2
2000	4000	±2,0
4000	6000	±3,0

Combination 00 standard order

After cutting, the shafts are only shortened and deburred, no further dressing of the end is carried out.

Combination 01 standard stage

The shafts are chamfered on both ends after the shortening, preventing the occurrence of damage to the ball cage or seals, in case of contact with the ball bushings.



Ød [mm]	4	5	6	8	10	12	16	20	25	30	35	40	50	60
l1 [mm]	1	1,5	1,5	1,5	1,5	2	2	2	2	2	2	3	3	3

Combination 02 axial thread



Ød [mm]	12	16	20	25	30	40	50
d1 [mm]	M5	M6	M8	M10	M12	M12	M16
t1 [mm]	12,5	16	19	22	28	28	36

Combination 03 axial thread and center bore, according to DIN 332-D



Ød [mm]	12	16	20	25	30	40	50
d1 [mm]	M5	M6	M8	M10	M12	M12	M16
t1 [mm]	12,5	16	19	22	28	28	36

Combination 04 radial holes (bores) with and without thread

In case steel shafts have to be supported, radial bores are necessary.



Ød [mm]	12	16	20	25	30	40	50
d1 [mm]	M4	M5	M6	M8	M10	M10	M12
t1 [mm]	2,5	2,5	3,0	3,0	3,5	4,0	4,0

The hole distance depends on the shaft diameter. The tables for the shaft supports display the reference data.

Combination 05

Axial thread (combination 02) and radial bores with and without thread (combination 04).

Combination 06

Axial thread and center bore, according to DIN 332-D (combination 03) and radial bores with and without thread (combination 04).

Examples of tooling

Please use your own customer drawing for a request, or copy our model and complete with the required data (values).

Insertion for locking ring, according to DIN 471



Insertion 90°



Width across flat



Width flat



Taps



1. Undercut to form F, DIN 509 (both sides)

Threaded ends



1. Thread runout to DIN 76-a1 (for undercut DIN 76-A)
2. Undercut to DIN 76-A (recommanded)

Taps and threaded ends



1. Undercut to DIN 76-A (recommanded)
2. Undercut to form F, DIN 509 (both sides)
3. Thread runout to DIN 76-a1 (for undercut DIN 76-A

Notch



Surface



NTN SNR With You

Type designation code

BBE... ball bushings and BBET... super ball bushings

- Examples of order reference for ball bushings/super ball bushings without seal: BBE20, BBET20
- Examples of order reference for a ball bushings/super ball bushings with single-sided seal: BBE20U, BBET20U
- Examples of order reference for a ball bushings/super ball bushings with double-sided seal: BBE20UU, BBET20UU

KH ball sleeves

- Example of order reference for a ball sleeve without seal: KH1228
- Example of order reference for a ball bushings with double-sided seal: KH1228LL/3AS

Linear units with standard ball bushings (norm)

- Example of order reference for linear units with standard BBE ball bushings with double-sided seal: LSE20UU

Linear units with super ball bushings

- Examples of order reference for linear units with super ball bushings with double-sided seal: LSET20UU

Shafts / hollow shafts

W 20 - 6000 - 0 - 04 - 04 - N37,5 - P1
1 2 3 4 5 6 7

1	W20	Type of shaft (W – solid shaft, HW- hollow shaft) and diameter (mm)	
2	6000	Length of shaft (mm)	
3	0	Material/finishing of the shaft/hollow shaft	
		0	Cf53 (für W), C60 (for HW)
		1	X90CrMoV18
		2	Cf53 hard-chrome plated
		3	X46Cr13
4	04	Shaft tooling (00…06, XX- according to design by customer)	
5	04	Shaft tooling (00…06, XX- according to design by customer)	
6	N37,5	N	measure [mm]
7	P1	P	measure [mm]
		P0	standard measure according to catalog for SR10, SR30, SR40
		P1	standard measure according to catalog for SR20
		P2	standard measure according to catalog for SR20

Position 6 and 7 only for the shaft tooling combination 04, 05 and 06!

Shaft supports with/without shaft

SR20 - 16 - 1199 - N37,5 - P1 - W - 0 - 04 - 04
1 2 3 4 5 6 7 8 9

1	SR20	Model of the mounting rail	
2	16	Diameter of the shaft (mm)	
3	1199	Length of the mounting rail (mm)	
4	N37,5	N	measure [mm]
5	P1	P	measure [mm]
		P0	standard measure according to catalog for SR10, SR30, SR40
		P1	standard measure according to catalog for SR20
		P2	standard measure according to catalog for SR20
6	W	without	without shaft
		W	solid shaft
		HW	hollow shaft
7	0	Material/finishing of the shaft/hollow shaft	
		0	Cf53 (für W), C60 (for HW)
		1	X90CrMoV18
		2	Cf53 hard-chrome plated
		3	X46Cr13
8	04	Shaft tooling (00…06, XX- according to design by customer)	
9	04	Shaft tooling (00…06, XX- according to design by customer)	

Position 6 to 9 only if with shaft/hollow shaft!

General information

Introduction

Linear ball bushings achieve longitudinal movement along a shaft by retaining the balls in a closed circulation path, allowing constant recirculation through the load zone. Hence, unlimited lifting heights/strokes are possible. The ball bushings offer the advantages of any journal (ball) bearing, namely a long operational life, low friction and breakaway torque, high precision and efficiency. The surfaces of the bearings are made from high-grade rolling bearing steel. The precisely shaped and polished cylindrical sheet-metal outer ring consists of one single part. It is held together by way of turned parts, screwed into the bushing/case and combining the function of smooth sealing rings through their design. Therefore, standard bearings with wiper seals can often be utilized. A unit with high rigidity, functional reliability and sustainability is achieved.

Load ratings

Dynamic load rating C

The radial load with constant magnitude and direction, a linear-rolling bearing can theoretically cope with for a nominal operational period of 10^5 m covered distance. Remark: The details of the dynamic load rating stipulate that the lift of the linear-joint (ball) bearings should be at least three times its overall constructional length.

Static load rating C_0

Static radial load results in deformation at the contact zones with the highest load/stress between the rolling element and the orbital path (shaft) of 5300 Mpa.

Remark: The permanent overall deformation of the rolling element and the orbital path corresponds approximately to a factor of 0,0001 of the diameter of the rolling element.

Permissible load

Comparison between permissible loads in standard ball bushings and tandem models

Type	dynamic load rating	static load rating	permissible static moment
BBE…*	1	1	1
BBE…L	1,6	2	~ 6

* for comparative purposes, standard type BBE is set as "1".

Closed and adjustable ball bushings

Number of rows of balls	4	5	6
C (load rating according to Table)			
C_{MAX} (maximal load capacity)			
Load coefficient C_{MAX}/C	1,414	1,463	1,280

The load capacity of a ball bearing (closed and adjustable) varies depending on the reference point of the load (and) on the circumference (size). The value in the Tables indicates the smallest load rating assuming a load working from/on the topside of a ball element. Where two ball elements are utilized that are being evenly loaded, the value increases. The Table above displays the values for the number of ball elements in each of the cases.

Open ball bushings

Number of rows of balls	3*	4	5
Load from above	 C_{0max}	 C_{0max}	 C_{0max}
Load from below	 $C_0=0,64C_{0max}$	 $C_0=0,54C_{0max}$	 $C_0=0,57C_{0max}$

* except the types with three rows, with a steel cage.

Where a load is applied in the open direction, the load capacity (rating) is reduced, because the load is working on a smaller number of rows of balls.

Material

Depending on the application, various models of ball bushings may be utilized.

Standard ball bushings of the BBE series consist of the following:

- a hardened and polished outer sleeve (100Cr6)
- a guidance cage made from plastic (POM)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

These ball bushings have as distinctive advantages for instance reduced noise during operation and a cost-efficient model.

Standard ball bushings of the BBE…A series consist of the following:

- a hardened and polished outer sleeve (100Cr6)
- a guidance cage made from austenitic stainless steel (X2CrNi 18-9)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

Potential applications: high temperatures, for instance in foundry applications or applications involving vacuum, where the utilization of plastic parts is not feasible.

The corrosion-resistant ball bushings of the BBES series consist of the following:

- a hardened and polished outer sleeve made from martensitic stainless steel (X105CrMo17)
- a guidance cage made from plastic (POM)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

Potential applications: corrosive environments.

The corrosion-resistant ball bushings of the BBES…A series consist of the following:

- a hardened and polished outer sleeve made from martensitic stainless steel (X105CrMo17)
- a guidance cage made from austenitic stainless steel (X2CrNi 18-9)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

The ball bushings of the BBES…A series are specifically intended for use under extremely dirty conditions, for instance cement works or the wood processing industry. A further potential area of application is the industry in which aggressive cleaning agents are used (e.g. the food industry, chemical industry, pharmaceutical and medicinal industry).

Super ball bushings of the BBET… series consist of the following:

- a guidance cage and outer sleeve made from POM
- hardened steel inserts with polished orbital path groove (15CrMo5)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

The high-grade super ball bushings of the BBET series distinguish themselves from the conventional ball bushings by a triple load capacity and by an operational life that is 27 times as long as the normal one.

The ball bushings of the KH… series consist of the following:

- a hardened sleeve, shaped without cutting (chipless)
- a guidance cage made from plastic (POM)
- balls made from ball-bearing steel (100Cr6)
- wiper seals made from NBR (optional)

Ambient temperature during operation

Material		Name	Temperature range
Outer sleeve	Cage		
Steel	Plastic	BBE…	-20°C ~ 80°C (-4°F ~ 176°F)
	Steel	BBE…A	-20°C ~ 110°C (-4°F ~ 230°F)
Stainless steel	Plastic	BBES…	-20°C ~ 80°C (-4°F ~ 176°F)
	Steel	BBES…A	-20°C ~ 140°C (-4°F ~ 284°F)*

*When using a ball bearing with seals, the ambient temperature should not exceed 120°C (248°F).

Service life

Nominal service life

The nominal service assumes a 90% certainty for achievable service life for a single rolling bearing or a group consisting of similar rolling bearings, running under the same conditions, with standard material of normal production quality and under standard operating conditions.

The sizing of the ball bearing is determined by the required service life and load. The service life of the ball bushings is calculated in the same manner as all rolling bearing, using the following formula:

$$L = \frac{C}{F} \bullet \frac{f_h \bullet f_T \bullet f_c}{f_w} \bullet 50$$

L nominal service life, km
C dynamic load rating, N
F dynamic load, N
f_H hardness factor of the shaft hardness (standard 1)
f_T temperature factor
f_C contact factor
f_W load factor

$$L_h = \frac{L}{2 \bullet s \bullet n_s \bullet 60}$$

L_h nominal service life, h
s stroke length, m
n_s stroke frequency, min^{-1}

Hardness factor for shaft hardness f_h



If shafts are utilized with a hardness of the surfaces of less than 60 HRC, a hardness factor is to be taken into account.

Temperature factor f_t



If the ambient temperature of the ball bushings exceeds 100°C (212°f) during operation, negative effects from the high temperatures must be taken into account. Moreover, the respective ball bearing has to be suited for high temperature ranges.

Contact factor f_C

If multiple ball bushings are put closely together, the running motion is influenced by moments and the mounting precision, in such a way that an equal load distribution is very hard to achieve. In such a case, a contact factor is to be taken into account.

Number of ball bushings closely put together	f_C
1	1,0
2	0,81
3	0,72
4	0,66
5	0,61

Load factor f_W

In general, machines with oscillating movements cause vibrations and shocks during their operation. Generally, it is quite hard to exactly determine the vibrations and shock loads, caused by repeated starting and stopping, during operation at high speeds. If the loads acting on the ball bushings cannot be measured or in case of high speed and shock loads having a large influence, the appropriate load factor has to be applied.

Operating conditions, speed V	f_w
Normal operating conditions, V≤0,25 m/s	1,0…1,5
Normal operating conditions with limited vibrations/shocks, 0,25<V≤1,0 m/s	1,5…2,0
Operating conditions with strong vibrations/shocks, V>2,0 m/s	2,0…3,5

Static safety coefficient f_S

The static safety factor is used to prevent unacceptable permanent deflections of the raceways and rolling elements. It is the relation between the static load capacity rating C_0 and the maximum occurring load F_0max. The maximum load condition including transient conditions is assumed.

$$f_s = \frac{C_0}{F_{0MAX}}$$

f_s static safety coefficient
C_0 static load rating, N
F_{0max} maximum static load, N

References for the static safety coefficient in case of various operating conditions:

Operating conditions	f_s
Normal operating conditions	1 ... 2
Limited shock loads and vibrations	2 ... 4
Moderate shock loads or vibrations	3 ... 5
Strong shock loads or vibrations	4 ... 6
Load parameters are unknown	6 ... 15

Lubrication and friction

The friction levels for ball bushings without wiper seals are quite low, at approx 0.001 to 0.003. The general rolling bearing criteria apply to the lubrication. Lubrication can be mineral based oil or grease and the following is to be taken into account. The grease enhances the sealing and adheres to the ball bearing. Further lubrication is only necessary over longer intervals. Contrary to ball screws and track rail guides, substantially less lubricant is required for ball bushing guides, due to the limited contact surface between the rolling bearing and the orbital path.

We recommend mineral based grease of K2K DIN 51825 quality. In case of loads that are more than 10% higher than the dynamic load capacity rating, greases with EP additives are to be used (KP2K DIN 51825). The ball bushings as standard are treated and delivered with an oily preservative. The preservative can be used with and can be combined with lubricants having an oily basis, so that in general the bearing does not have to be washed before installation.

Under normal circumstances, grease SNR LUB EP is used. Specific requirements under certain environmental conditions require the use of suitable grease. In vacuum applications, lubricants are required that have a lower evaporation rate, in order to keep the vacuum atmosphere in good order. In the food industry and cleaning room, there are special requirements for the lubricant with regard to emission and compatibility. Basically the compatibility of the lubricants in relation to each other should be checked. In case of special ambient conditions, we will gladly assist you.

Designation	Type of oil, consistency regulator	NLGI class DIN 51818	Walkpenetration DIN ISO 2137 at 25°C (77°F)	Base oil-viscosity DIN51562 at 40°C (104°F)	Density	Temperature range	Properties	Range of application
			[0,1 mm]	[mm²/s]	[kg/m³]	[°C]		
SNR LUB Heavy Duty	paraffinic mineral oil / lithium-special-soap	2	285	apx. 105	890	-30…+110	- low friction - Smooth running	- general mechanical engineering
SNR LUB GV+	sythetic ‚KW' oil / ester oil / lithium-spezial-soap	2	265…295	24	900	-50…+120°C (-58°F...248°F)	- very good adhesive power - highly water-resistant	- high speeds
SNR LUB HIGH TEMP	sythetic KW-oil / mineral oil / polyurea	2	265…295	160	900	-40…+160°C (-40°F...320°F)	- high heat resistance - good corrosion protection - high oxidation resistance	- high temperature range
SNR LUB FOOD	paraffinic mineral oil / aluminium complex soap	2	265…295	apx. 240	920	-30…+110	- good corrosion protection - very good adhesive power - high water resistance - NSF H1 registered*	- Food industry
Microlub GL261	mineral oil / lithium-special-soap	1	310…340	280	890	-30…+140	- good wear protection - highly pressure-resistant - Additive against fretting corrosion	- general mechanical engineering - heavy load - Short-stroke applications - Vibrations
Klübersynth BEM34-32	sythetic 'KW' oil / special - calcium soap	2	265…295	apx. 30	890	-30…+140	- highly pressure-resistant - good wear protection - good durability - low starting torque	- Clean room applications
Klübersynth UH1 14-151	sythetic 'KW' oil / ester oil / aluminium - complex soap	1	310…340	apx. 150	920	-45…+120	- good corrosion protection - good durability - high water resistance - NSF H1 registered*	- Pharmaceutical industry - Food industry

* This grease is registered as H1 product: it has been developed for occasional, technically unavoidable contact with foodstuff. Experiences have shown that the grease can also be used for the corresponding applications in the pharmaceutical and cosmetic industry, on the conditions listed in the product information. However, there are no specific test results, for instance, on the biocompatibility, as may be required under certain circumstances in the pharmaceutical area. Therefore, before it is used in this area by equipment manufacturers and distributors, corresponding risk analyses must be performed. If necessary, measures to avoid health hazard and injuries must be taken. (Source: Klüber Lubrication).

In case of the initial lubrication and further lubrication through the lubricating hole, lubricant has to be applied to the bearing in installed shafts until it abundantly 'fills' the bearing.

The lubrication period depends on many influential factors, for instance:
- Load
- Speed
- Motion sequence
- Temperature

The following influential factors reduce the lubrication interval:
- Greater load
- High speed
- Short stroke (stroke is shorter than three times the length of the ball bearing)
- Lower ageing resistance of the lubricant

Precise lubrication intervals can be obtained upon request, based on the operating conditions.

Fittings

In general, in case of standard ball bushings, the normal clearance fit is applied. The transition fit is used, in order to reduce the play and increase the accuracy.

The pre-tension for the adjustable and open ball bushings must be set according to the values displayed in the table for the radial play (clearance), so that the allowable limit values for the pre-tension cannot be exceeded.
In case of the super ball bushings, it has to be taken into account that adequate play (clearance) occurs between the super ball bearing and the shaft. If that is not the case, early failure and/or jerky movements may be caused.

Series	Shaft		Casing	
	Clearance fit	Transition fit	Clearance fit	Transition fit
BBE…	h6	j6	H7	J7
BBE…L	h6	-	H7	-
BBER…	h6	j6	-	-
BBER…L	h6	-	-	-
BBET…	h6	-	H7	-

Standard ball bushings are otherwise inserted in a H7 bore and retained by way of locking rings. Alternatively, they can and may also be fixed or adhered by way of screwed disks, locking plates or washers.

Using complete bearing units in which the bearings have already been installed eliminates fitting concerns and offers a significant cost benefit.

More information concerning our NTN-SNR products for linear motion is provided in our catalogues.

NTN-SNR Linear Motion
Linear modules

NTN-SNR Linear Motion
Ball screws

NTN-SNR Linear Motion
Linear axis news

NTN-SNR Linear Motion
Ball splines

NTN-SNR Linear Motion
We get you moving

www.ntnsnr.ru snr-mail@ya.ru Тел.: (499) 703-40-50

NTN-SNR LINEAR MOTION:
BALL BUSHINGS

DOC.I_BBUSHING_CAT1.GBa - SAP-Code: 360450 - Non contractual document - NTN-SNR Copyright International 05/2015 Printed in France

This document is the exclusive property of NTN-SNR ROULEMENTS. Any total or partial reproduction hereof without the prior consent of NTN-SNR ROULEMENTS is strictly prohibited. Legal action may be brought against anyone breaching the terms of this paragraph.

NTN-SNR ROULEMENTS shall not be held liable for any errors or omissions that may have crept into this document despite the care taken in drafting it. Due to our policy of continuous research and development, we reserve the right to make changes without notice to all or part of the products and specifications mentioned in this document.

© NTN-SNR ROULEMENTS, international copyright 2016

NTN-SNR ROULEMENTS - 1 rue des Usines - 74000 Annecy
RCS ANNECY B 325 821 072 - Code APE 2815Z - Code NACE 28.15
www.ntn-snr.com

NTN SNR With You